

FEP OUTPUT FORMAT TELEMETRY DATA DISTRIBUTION OBJECTS

OVERVIEW

Telemetry data received directly from the FEP will be delivered via telemetry packet objects. The format for these objects and the data they contain is referred to as the FEP Output Format (FOF). Data produced by the Front End Processor is similar to Common Data Format (CDF) with the following differences: (1) the CDF Header Object contains only one time field, the Spacecraft Time; (2) the CDF Element Object contains an 8-character Mnemonic ID and the FOF does not; and (3) the EU Value in the CDF Element Object can have different formats as indicated by an EU Type field. The two additional time fields in the FOF are used for the merge process, but are not archived with the telemetry.

An Application Program Interface (API) will be provided to isolate user from format concerns. The API will contain all the necessary methods for extracting data and presenting it to the user.

DETAILS

Each telemetry object consists of a single telemetry data packet. Each packet will consist of a header object containing meta-data about the packet followed by telemetry element objects. Each telemetry element object contains one spacecraft telemetry or derived parameter in both raw and Engineering Unit formats, along with its numeric identifier and associated flags.

There is a packet for each unique spacecraft time for which telemetry data is received. For 4 Kbps telemetry, this is one packet per minor frame; for 32 Kbps data, it's two packets per minor frame. The data stream consists of a sequence of packets each consisting of a header corresponding to a specific spacecraft time followed by a telemetry element object for each decommutated parameter sampled at that time.

Descriptions of the Telemetry Data Objects are provided in the Table1 below.

Table 1. Definitions of Fields in the FOF

Item Name	Bit Size	Type	Item Description
FOF Packet Header Object			
Spacecraft Time	64	IEEE Flt. Pnt.	Time defined by the vehicle clock count converted to UTC and expressed as modified Astronomical Julian Day. For test data, this field will contain CCS Time when presented to the user if the data capture process was configured to store the data by CCS time during the test.
NGT Receipt Time	64	IEEE Flt. Pnt.	UTC of time NGT transmitted the data to CCS expressed as modified Astronomical Julian Day
CCS Receipt	64	IEEE	UTC of time data was received by CCS expressed as

Item Name	Bit Size	Type	Item Description
Time		Flt. Pnt.	modified Astronomical Julian Day
Number of Elements	16	positive integer	Number of Telemetry Element Objects in the packet
Data Source	8	bits	Identifies various characteristics of the data source as shown in Table 2.
Telemetry Format	8	positive integer	Identifies telemetry format. Integer codes between 0 and 255 will be assigned to all existing formats as shown in Table 3. Additional codes will be assigned for new formats as necessary.
FOF Element Object			
Numeric ID	16	positive integer	Unique identifier for the parameter
Raw Value	32	raw Tlm. bits	Parameter raw value as stored by the spacecraft
EU Value	32	IEEE Flt. Pnt.	Parameter value converted to engineering units.
Flags	16	bits	Associated flags (see Table 4)

Notes

1. Numeric ID: This is a unique integer assigned to each telemetry point for the life of the mission even if the point is eliminated.
2. Data gaps are identified in two ways. At the data stream level, a Boolean pseudo-parameter is used that indicates data presence or absence. The gap pseudo-parameter is set to 1 if no data is received for a period of time greater than some threshold which could be one minor frame interval or some longer period of time (**TBD**). The gap pseudo-parameter will change value at the beginning and end of each contiguous data span. At the element level, the Initial Point Flag and Final Point Flag indicate the beginning and end of contiguous data spans for a single element. There may be a gap in an element, even though the gap pseudo-parameter never indicates a gap in the data stream, if a portion of a minor frame is lost. It remains to define the interval thresholds used to set the gap flags and the gap pseudo-parameter. The precise definition of a data gap is **TBD**.
3. The data source flags are all set in the FEP and are transferred from the FOF to the CDF unchanged.

Table 2. Definitions of Flags in the FOF/CDF Header Data Source Field

BIT	FLAG NAME	DESCRIPTION
0 (lsb)	Spacecraft Data Mode	0 indicates recorded data (ETR/SSR) 1 indicates Real-Time data
1	Ground Station Mode	0 indicates direct feed through ground station 1 indicates replay of ground station recorded data
2	CCS Mode	0 indicates operational data 1 indicates test data
3	FEP Mode	0 indicates external data source 1 indicates FEP is replaying pre-recorded data for testing
4	FEP Replay	Set to 1 if data is being supplied in response to an FEP replay request
5	Era	0 if data was captured by CCS 1 if data was converted AEDP/ESS data
6-7	Spare	

Table 3. Telemetry Format Identifier Code Definitions for the FOF/CDF Header

Code	Format	Code	Format	Code	Format	Code	Format
0	off	37	HF	80	PN	163	U
5	XN	40	FN	81	PF	186	ZN
6	XF	41	FF	82	NSSC-1 Dump	187	ZF
24	TN	48	C	138	M	192	AN
25	TF	64	YN	145	S	193	AF
36	HN	65	YF	146	D/E	others	spare

Table 4. Definitions of Flag Bits in the FOF/CDF Element Flags Field

BIT	FLAG NAME	SET BY	DESCRIPTION
0 (lsb)	Corrected Spacecraft Time	FEP and Merge	Set to 1 if VCC was bad and S/C Time has been corrected; also used for D/E format data
1	Quality	FEP	Set to 1 if data quality is questionable
2	Limit Low	FEP	Set to 1 if out of limits low
3	Limit High	FEP	Set to 1 if out of limits high
4	Limit Level	FEP	Set to 1 if beyond severe limit (red)
5	Delta Error	FEP	Set to 1 if delta limit exceeded
6	Alternate limits	FEP	Set to 1 if alternate limits should be used
7	EU Conversion Error	FEP	Set to 1 for conversion error
8	No EU Conversion	FEP	Set to 1 if no EU conversion is defined in the PRD for this element
9	Initial Point	FEP	Set to 1 if first point after gap, start of contiguous span
10	Final point	Merge	Set to 1 if last point before gap, end of contiguous span
11	Reconstructed Point	Data Mgt	Set to 1 if this point was added to "changes only" data to construct "all points" data.
12-15	Spare		